



PRICE LIST

Please check shipping code, STK = Stock Item, 3DAY = Ships in 3 business days

EZSeries Touchpanel Operator Interfaces

Part Number	Ship	Price
4" Monochrome Page 3-61		
EZ-S4M-FS: EZSeries Touchpanel operator interface with 3.8" STN Monochrome display, NEMA 4,4x (indoor), 48 cell resistive touch screen. All the serial drivers are supported (No hardware network drivers, No real-time clock, No flash card).	STK	\$199
EZ-S4M-FE: EZSeries Touchpanel with, 3.8" STN Monochrome display, NEMA 4,4x (indoor), 48 cell resistive touch screen, Ethernet/IP interface. All the serial drivers are supported (No hardware network drivers, No real-time clock, No flash card).	STK	\$299
3.5" TFT Color Page 3-62		
EZ-T4C-FS: EZSeries Touchpanel operator interface with 3.5" TFT Color display, NEMA 4,4x (indoor), 48 cell resistive touch screen. All the serial drivers are supported (No hardware network drivers, No real-time clock, No flash card).	STK	\$299
EZ-T4C-FE: EZSeries Touchpanel with 3.5" TFT Color display, NEMA 4,4x (indoor), 48 cell resistive touch screen, Ethernet/IP interface. All the serial drivers are supported (No hardware network drivers, No real-time clock, No flash card).	STK	\$399
6" White On Blue Page 3-63		
EZ-S6W-RS: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), with 48 cell resistive touch screen, 256 KB of RAM (non-expandable), and 20-30VDC operating range. All the serial drivers are supported and the panel does not provide support for Ethernet Option Cards.	STK	\$369
EZ-S6W-RSU: EZSeries Touchpanel with Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 touch cells, 256 KB of RAM (non-expandable), and 20-30VDC operating range. Panel has Universal Ethernet Port built-in for Ethernet/IP, DF1 over Ethernet, Modbus TCP/IP, and GE SRTP only and does NOT include support for serial drivers.	STK	\$798
6" Monochrome Page 3-64, 3-65		
EZ-S6M-F: EZSeries Touchpanel operator interface with 5.7" STN Monochrome display, NEMA 4,4x (indoor), Bubble bezel, 48 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB), and 20-30VDC operating range. Accepts optional 512K, 1MB, or 2 MB compact flash cards. All the serial drivers are supported.	STK	\$479
EZ-S6M-FH: EZSeries Touchpanel with 5.7" STN Monochrome display, NEMA 4,4x (indoor), 48 touch cells, 512 KB of RAM (expandable to 1.5MB), and 20-30VDC operating range, A-B DH+ or Remote I/O interface. Optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via DH+ or Remote I/O.	STK	\$979
EZ-S6M-R: EZSeries Touchpanel operator interface with 5.7" STN Monochrome display, NEMA 4,4x (indoor), Bubble bezel, 48 cell resistive touch screen, 256 KB of RAM (non-expandable), and 20-30VDC operating range. All the serial drivers are supported and the panel does not provide support for Ethernet Option Cards.	STK	\$399
EZ-S6M-ES: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 48 cell resistive touch screen, 256 KB of RAM (non-expandable), and 20-30VDC operating range. Only EZProtocols (for EZAutomation) are supported and the panel does not provide support for Ethernet Option Cards.	STK	\$399
EZ-S6M-RS: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 48 cell resistive touch screen, 256 KB of RAM (non-expandable), and 20-30VDC operating range. All the serial drivers are supported only and the panel does not provide support for Ethernet Option Cards.	STK	\$399
EZ-S6M-FS: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range. Accepts optional 512K, 1MB, or 2 MB compact flash cards. All the serial drivers are supported.	STK	\$449
EZ-S6M-FSC: EZSeries Touchpanel with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, CCLink interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via CCLink.	3DAY	\$1,049
EZ-S6M-FSD: EZSeries Touchpanel with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, DeviceNet interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via DeviceNet.	3DAY	\$1,049
EZ-S6M-FSE: EZSeries Touchpanel with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, Ethernet/IP interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via Ethernet/IP.	3DAY	\$1,049
EZ-S6M-FSH: EZSeries Touchpanel with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 touch cells, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, A-B DH+ or Remote I/O interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via DH+ or Remote I/O.	3DAY	\$1,049
EZ-S6M-FSM: EZSeries Touchpanel with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, MODBUS interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via MODBUS Plus.	3DAY	\$1,049
EZ-S6M-FSP: EZSeries Touchpanel with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, Profibus interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via Profibus.	3DAY	\$1,049
EZ-S6M-FST: EZSeries Touchpanel with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 touch cells, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, MODBUS TCP/IP interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via MODBUS TCP/IP.	3DAY	\$849
EZ-S6M-FSU: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, Universal Ethernet Port. Accepts optional 512K, 1MB, or 2 MB compact flash cards.	3DAY	\$848
EZ-S6M-RMC: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, Remote Monitoring & Control (RMC) card installed. Accepts optional 512K, 1MB, or 2 MB compact flash cards.	3DAY	\$599
6" STN Color Page 3-66, 3-67		
EZ-S6C-F: EZSeries Touchpanel operator interface with 5.7" STN Color display, NEMA 4,4x (indoor) front, Bubble bezel, 48 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB), and 20-30VDC operating range. Accepts optional 512K, 1MB, or 2 MB compact flash cards. All the serial drivers are supported.	STK	\$699
EZ-S6C-FH: EZSeries Touchpanel with 5.7" STN Color display, NEMA 4,4x (indoor) front, Bubble bezel, 48 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB), and 20-30VDC operating range, A-B DH+ or Remote I/O interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via DH+ or Remote I/O.	3DAY	\$1,199
EZ-S6C-K: EZSeries Touchpanel operator interface with 5.7" STN Color display, NEMA 4,4x (indoor) front, Bubble bezel, 48 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB), and 20-30VDC operating range. Accepts optional 512K, 1MB, or 2 MB compact flash cards. Only DirectLOGIC PLC protocols (for Automation Direct) are supported.	STK	\$699
EZ-S6C-KS: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range. Accepts optional 512K, 1MB, or 2 MB compact flash cards. Only DirectLOGIC PLC protocols (for Automation Direct) are supported.	STK	\$649
EZ-S6C-FS: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range. Accepts optional 512K, 1MB, or 2 MB compact flash cards. All the serial drivers are supported.	STK	\$649
EZ-S6C-FSC: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, CCLink interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via CCLink.	3DAY	\$1,299
EZ-S6C-FSD: EZSeries Touchpanel with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, DeviceNet interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via DeviceNet.	3DAY	\$1,299
EZ-S6C-FSE: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, Ethernet/IP interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via Ethernet/IP.	3DAY	\$1,299
EZ-S6C-FSH: EZSeries Touchpanel with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 touch cells, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, A-B DH+ or Remote I/O interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via DH+ or Remote I/O.	3DAY	\$1,299
EZ-S6C-FSM: EZSeries Touchpanel with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, MODBUS Plus interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via MODBUS Plus.	3DAY	\$1,299
EZ-S6C-FSP: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, Profibus interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via Profibus.	3DAY	\$1,299
EZ-S6C-FST: EZSeries Touchpanel with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, MODBUS TCP/IP interface. Accepts optional 512K, 1MB, or 2 MB compact flash cards. The panel also provides support for all the serial drivers when not communicating via MODBUS TCP/IP.	3DAY	\$1,069
EZ-S6C-FSU: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, Universal Ethernet Port. Accepts optional 512K, 1MB, or 2 MB compact flash cards. Does NOT include support for serial drivers.	3DAY	\$1,098
EZ-S6C-RMC: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range, Remote Monitoring & Control (RMC) card installed. Accepts optional 512K, 1MB, or 2 MB compact flash cards.	3DAY	\$799
6" TFT Color Page 3-68		
EZ-T6C-FS: EZSeries Touchpanel operator interface with Slim Bezel, 5.7" TFT Color display, NEMA 4,4x (indoor), 192 cell resistive touch screen, 512 KB of RAM (expandable to 1.5MB) and 20-30VDC operating range. Accepts optional 512K, 1MB, or 2 MB compact flash cards. All the serial drivers are supported.	STK	\$769



EZseries CE Touchpanel

Part Number	Ship	Price
EZC-T8C-EP: EZSeries CE Touchpanel with Slim Bezel, 8.2" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. Profibus interface. The panel also provides support for all the serial drivers when not communicating via Profibus.	3DAY	\$2,599
EZC-T8C-EC: EZSeries CE Touchpanel with Slim Bezel, 8.2" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. CCLink interface. The panel also provides support for all the serial drivers when not communicating via CCLink.	3DAY	\$2,199
EZC-T8C-EU: EZSeries CE Touchpanel with Slim Bezel, 8.2" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, and 20-30VDC operating range. Universal Ethernet Port built-in for Ethernet/IP, DF1 over Ethernet, Modbus TCP/IP, and GE SRTP. No support for serial drivers.	3DAY	\$2,098
10" TFT Color		Page 3-71
EZC-T10C-E: EZSeries CE Touchpanel with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. All the serial drivers are supported.	3DAY	\$1,499
EZC-T10C-ED: EZSeries CE Touchpanel with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. DeviceNet interface. The panel also provides support for all the serial drivers when not communicating via DeviceNet.	3DAY	\$2,899
EZC-T10C-EH: EZSeries CE Touchpanel with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, and 20-30VDC operating range. A-B Data Highway Plus (DH+) or Remote I/O interface. The panel also provides support for all the serial drivers when not communicating via DH+ or Remote I/O.	3DAY	\$2,499
EZC-T10C-EM: EZSeries CE Touchpanel with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. MODBUS Plus interface. The panel also provides support all the serial drivers when not communicating via MODBUS Plus.	3DAY	\$2,499
EZC-T10C-EP: EZSeries CE Touchpanel with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. Profibus interface. The panel also provides support for all the serial drivers when not communicating via Profibus.	3DAY	\$2,899
EZC-T10C-EC: EZSeries CE Touchpanel with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. CCLink interface. The panel also provides support for all the serial drivers when not communicating via CCLink.	3DAY	\$2,499
EZC-T10C-EU: EZSeries CE Touchpanel with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, and 20-30VDC operating range. Universal Ethernet Port built-in for Ethernet/IP, DF1 over Ethernet, Modbus TCP/IP, and GE SRTP. No support for serial drivers.	3DAY	\$2,398
15" TFT Color		Page 3-72
EZC-T15C-E: EZSeries CE Touchpanel with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. All the serial drivers are supported.	3DAY	\$2,199
EZC-T15C-ED: EZSeries CE Touchpanel with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. DeviceNet interface. The panel also provides support for all the serial drivers when not communicating via DeviceNet.	3DAY	\$3,699
EZC-T15C-EH: EZSeries CE Touchpanel with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. A-B Data Highway Plus (DH+) or Remote I/O interface. The panel also provides support for all the serial drivers when not communicating via DH+ or Remote I/O.	3DAY	\$3,299
EZC-T15C-EM: EZSeries CE Touchpanel with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. MODBUS Plus interface. The panel also provides support all the serial drivers when not communicating via MODBUS Plus.	3DAY	\$3,299
EZC-T15C-EP: EZSeries CE Touchpanel with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. Profibus interface. The panel also provides support for all the serial drivers when not communicating via Profibus.	3DAY	\$3,699
EZC-T15C-EC: EZSeries CE Touchpanel with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. CCLink interface. The panel also provides support for all the serial drivers when not communicating via CCLink.	3DAY	\$3,299
EZC-T15C-EU: EZSeries CE Touchpanel with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net 4.2 Professional Plus, Nema 4.4x (indoor) front, Analog Resistive touch screen, AMD 333 Mhz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, and 20-30VDC operating range. Universal Ethernet Port built-in for Ethernet/IP, DF1 over Ethernet, Modbus TCP/IP, and GE SRTP. No support for serial drivers.	3DAY	\$3,198

EZSeries Touchpanel, CE Touchpanel Software & Accessories

Part Number	Ship	Price
EZSeries Touchpanel Manual, Programming Software and Cables		Page 3-54
EZ-PANEL-M: Hardware and Installation manual for EZSeries Touchpanel operator interfaces	STK	\$20
EZ-PGMCBL: EZSeries Touchpanel and EZCE Touchpanel programming software cable	STK	\$20
EZ-PANELEDIT: EZSeries Touchpanel and EZCE Touchpanel Programming Software CD	STK	\$99
EZC-TOUCHPANEL-M: Hardware and Installation manual for EZCE Touchpanel operator interfaces. Note: EZC-Touchpanel-M Hardware and User Manual included with every EZCE Touchpanel	3DAY	\$20
EZSeries Touchpanel, EZSeries Textpanel, and EZCE Touchpanel Communication Cables		Page 3-54
EZ-CBL: 10' RS232C shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to EZPLC. 15 pin D-shell male connector to 9 pin D-shell male connector.	STK	\$20
EZ-2CBL: 10' RS232C shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to DL05, DL06, DL105, DL205, D3-350 or D4-450 CPU. 15 pin D-shell male connector to RJ 12 modular connector.	STK	\$20
EZ-2CBL-1: 10' RS232C shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to a DL06, D2-250(-1) or D2-260 (bottom port) CPU. 15 pin D-shell male connector to 15 pin male HD.	STK	\$20
EZ-3CBL: 10' RS232C shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to a D3-340 CPU top or bottom port. 15 pin D-shell male connector to RJ11 modular connector.	STK	\$20
EZ-4CBL-1: 10' RS232C shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel panel to DL 405 (top port) CPU. 15 pin D-shell male connector to 15 pin D-shell male connector.	STK	\$20
EZ-4CBL-2: 10' RS 232C shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to a D2-DCM, D3-350 (bottom port), a D3-232-DCU installed on D3-333 or D3-340, or DL 405 (bottom point) CPU. 15-pin D-shell male to 25 pin D-shell male.	STK	\$20
EZ-MLOGIX-CBL: 6' shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to an AB Micrologix 1000, 1200, or 1500 CPU. 15 pin D-shell male connector to 8 pin DIN connector.	STK	\$25
EZ-SLC-232-CBL: 10' RS232C shielded cable to connect any EZSeries Touchpanel & Textpanel to an AB SLC 5/03, 5/04 or 5/05 CPU with DF-1 port. 15 pin D-shell male connector to 9 pin D-shell female connector.	STK	\$20
EZ-PLC5-232-CBL: 10' RS232C shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to an AB PLC5 CPU with DF1 port. 15 pin D-shell male connector to 25 pin D-shell male connector.	STK	\$20
EZ-DH485-CBL: 10' RS232C shielded cable to connect any EZSeries Touchpanel or CE Touchpanel to an AB SLC 500 CPU with a DH485 port and 747-A/C Module.	STK	\$22
EZ-90-30-CBL: 10' RS232C shielded cable to connect any EZSeries Touchpanels & Textpanel to GE Fanuc Series 90/30, 90/70 serial port using SNPX protocol. 15 pin D-shell male connector to 15 pin D-shell male connector.	STK	\$20
EZ-MITSU-CBL: 10' RS422 shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to Mitsubishi FX series CPU. 15 pin D-shell male connector to 25 pin D-shell male connector.	STK	\$20
EZ-MITSU-CBL-1: 10' RS422 shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to Mitsubishi FX series CPU. 15 pin D-shell male connector to 8 pin min. din.	STK	\$20
EZ-S7MPI-CBL: 10' shielded cable to connect any EZSeries Touchpanel, Textpanel or CE Touchpanel to Siemens Simatic S7 series CPU. 15 pin D-shell male connector to 9 pin D-shell connector.	STK	\$20
EZ-OMRON-CBL: 10' RS232C shielded cable to connect any EZSeries Touchpanels & Textpanel to Omron C200 or C500 with Hostlink protocol. 15 pin D-shell male connector to 25 pin D-shell male connector.	STK	\$20
EZ-ARCOL-CBL: 10' RS232C shielded cable to connect anyEZSeries Touchpanel, Textpanel or CE Touchpanel to Aromat PLC. 15 pin D-Shell male connector to 5 pin mini DIN male connector.	STK	\$20
EZ-CTRLUNI-CBL: 10' RS422 shielded cable to connect any EZTouch or EZSeries CE Touchpanel to Control Techniques Unidrive 4-wire. 15 pin D-Shell male connector to 9 pin D-shell female connector.	STK	\$20

EZSeries Touchpanel, CE Touchpanel Software & Accessories

Part Number	Ship	Price
EZ-CTRLUNI-CBL-1: 10' RS485 shielded cable to connect any EZTouch or EZSeries CE Touchpanel to Control Techniques Unidrive 2-wire. 15 pin D-Shell male connector to 9 pin D-shell female connector.	STK	\$20
EZ-CTCBI-CBL: 10' RS232 shielded cable to connect any EZTouch or EZSeries CE Touchpanel to Control Technology Corp (CTC) PLC. 15 pin D-Shell male connector to RJ12 connector.	STK	\$20
EZ-IDECM-CBL: 10' RS485 shielded cable to connect any EZTouch or EZSeries CE Touchpanel to IDEC Micro 3 PLC. 15 pin D-Shell male connector to 8 pin mini-din connector.	STK	\$20
EZ-MODUNI-CBL: 10' RS485 shielded cable to connect any EZTouch or EZSeries CE Touchpanel to Modicon Uni-Telway Telemecanique TSX 37 Micro PLC. 15 pin D-Shell male connector to 8 pin mini DIN connector.	STK	\$20
EZ-MODRTU-CBL: 10' RS232C shielded cable to connect anyEZSeries Touchpanel, Textpanel or CE Touchpanel to Modicon Modbus RTU. 15 pin D-Shell male connector to 9 pin D-shell male connector.	STK	\$20
EZ-S7200-CBL: 10' RS485 shielded cable to connect any EZTouch or EZSeries CE Touchpanel to Siemens S7 200 PLC. 15 pin D-Shell male connector to 9 pin D-shell male connector.	STK	\$20
EZ-SYMAX-CBL: 10' RS422 shielded cable to connect EZTouch, or EZSeries CE Touchpanel to Square-D symax. 15 pin D-Shell male connector to 9 pin D-shell male connector.	STK	\$20
EZ-TX505-CBL: 10' RS232C shielded cable to connect anyEZSeries Touchpanels or Textpanel connect to Texas Instrument 505 Series PLC. 15 pin D-Shell male connector to 9 pin D-shell female connector.	STK	\$20
EZ-IDECs-CBL: 10' RS232C shielded cable to connect anyEZSeries Touchpanel, Textpanel or CE Touchpanel to IDEC Micro Smart PLC. 15 pin D-Shell male connector to 8 pin mini DIN male connector.	STK	\$20
EZ-TX545-CBL: 10' RS422 shielded cable to connect anyEZSeries Touchpanel, Textpanel or CE Touchpanel to Texas Instrument 545-1102 series PLC. 15 pin D-Shell male connector to 9 pin D-shell male connector.	STK	\$20
EZ-TX545-CBL1: 10' RS422 shielded cable to connect anyEZSeries Touchpanel, Textpanel or CE Touchpanel to Texas Instrument 545-1104 PLC. 15 pin D-Shell male connector to 9 pin D-shell female connector.	STK	\$20
EZ-MODRJ-CBL: 10' RS232 shielded cable to connect any EZTouch or EZSeries CE Touchpanel to Modicon Micro PLC. 15 pin D-Shell male connector to RJ45 connector.	STK	\$20
EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer Accessories		Page 10-10
EZ-PANEL-M: Hardware and Installation manual for EZSeries Touchpanel operator interfaces. This manual is included with every panel.	STK	\$20
EZC-TOUCHPANEL-M: Hardware and Installation manual for EZSeries CE Touchpanel operator interfaces. This manual is included with every panel.	STK	\$20
EZTCC-COMPUTER-M: Hardware and Installation manual for EZSeries CE Touch Computer. Note: Hardware and Installation included with every CE Computer.	STK	\$20
EZ-RAM-1: 512K RAM Card for EZSeries Touchpanel operator interfaces only.	STK	\$50
EZ-RAM-2: 1MB expansion RAM card for EZSeries Touchpanel operator interfaces only.	STK	\$97
EZ-FLASH-1: 512K flash memory card for non-volatile user-program storage for EZSeries Touchpanel operator interfaces only.	STK	\$46
EZ-FLASH-2: 1MB flash memory card for non-volatile user-program storage for EZSeries Touchpanel operator interfaces only.	STK	\$56
EZ-FLASH-3: 2MB flash memory card for non-volatile user-program storage for EZSeries Touchpanel operator interfaces only.	STK	\$80
EZ-ETHERNET: Ethernet (10BaseT) communication interface card for EZSeries Touchpanel operator interfaces only. Works with H2 and H4-ECOM ethernet modules for Automation Direct's DL205 and DL405 PLCs (compatible with -F and -FS EZTouch operator interfaces only). Manual included with option card.	STK	\$190
EZ-ETHERPLUS: ModBus TCP/IP Ethernet communication interface card for EZSeries Touchpanel operator interfaces only for 10BaseT network connection. Manual included with option card.	STK	\$240
EZ-BAT: Replacement 1/2 AA, 3.6 volt lithium battery for EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$20
EZ-BRK-1: Optional DIN rail clips. Only for 6" models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer (package of 2).	STK	\$15
EZ-COMCON3: 15-pin male D-sub connectors with terminal blocks, for connecting RS422 network cable to EZ Products	STK	\$19
EZ-PANEL6-GSK: Replacement gasket for 6-inch EZSeries Touchpanel operator interface (standard, NON-SLIM) bezels only.	STK	\$8
EZ-PANEL8-GSK: Replacement gasket for 8-inch EZSeries Touchpanel operator interface (standard, NON-SLIM) bezels only.	STK	\$8
EZ-PANEL10-GSK: Replacement gasket for 10-inch EZSeries Touchpanel operator interface (standard, NON-SLIM) bezels only.	STK	\$8
EZ-PANEL-STUDS: Spare mounting studs for for EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer panels. Comes in package of 8 with nuts.	STK	\$8
EZ-6SLIMF-GSK: Replacement gasket for Slim Bezel 6 inch models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer.	STK	\$8
EZ-8SLIMF-GSK: Replacement gasket for Slim Bezel 8 inch models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer.	STK	\$25
EZ-10SLIMF-GSK: Replacement gasket for Slim Bezel 10 inch models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer.	STK	\$30
EZ-15SLIMF-GSK: Replacement gasket for Slim Bezel 15 inch models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer.	STK	\$34
EZ-COV6: Pack of 3 protective shields for 6 inch models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$20
EZ-COV8: Pack of 3 protective shields for 8 inch models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$34
EZ-COV10: Pack of 3 protective shields for 10 inch models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$38
EZ-COV15: Pack of 3 protective shields for 15 inch models of EZSeries Touchpanel, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$56
EZSeries Textpanel		
EZ-220: EZSeries Textpanel with 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, built-in menu system with adjusting arrows, data scrolling, data setpoint and display, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, dynamic decimal point option with read/write messages, and 20-30 VDC operating range. All serial drivers supported.	STK	\$169 Pg 4-14
EZ-220L: EZSeries Textpanel with 2 Line x 20 LARGE character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, built-in menu system with adjusting arrows, data scrolling, data setpoint and display, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, dynamic decimal point option with read/write messages, and 20-30 VDC operating range. All serial drivers supported.	STK	\$219 Pg 4-14
EZ-420: EZSeries Textpanel with 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, built-in menu system with adjusting arrows, data scrolling, data setpoint and display, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, dynamic decimal point option with read/write messages, and 20-30 VDC operating range. All serial drivers supported.	STK	\$189 Pg 4-14
EZ-220P: EZSeries Textpanel with 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, Numeric KEYPAD, five user defined pushbuttons with LED Indicators, built-in menu system with adjusting arrows, data scrolling, data setpoint and display, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, dynamic decimal point option with read/write messages, and 20-30 VDC operating range. All serial drivers supported. EZ-TEXT-M manual included with the panel.	STK	\$229 Pg 4-15
EZ-SP: EZText Setpoint Interface with 8 digit Numeric LED display, 16 character LCD display programmable with up to 256 data points with 16 character description per data point, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust for data and display, and 20-30 VDC operating range. All the serial drivers are supported.	STK	\$229 Pg 4-16
VFD Models		
EZ-220V: EZSeries Textpanel with 2 Line x 20 character Vacuum Fluorescent Display (VFD), Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, built-in menu system with adjusting arrows, data scrolling, data setpoint and display, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, dynamic decimal point option with read/write messages, and 20-30 VDC operating range. All serial drivers supported.	STK	\$269 Pg 4-14
EZ-220PV: EZSeries Textpanel with 2 Line x 20 character Vacuum Fluorescent Display (VFD), Nema 4,4x (indoor) front, Numeric KEYPAD, five user defined pushbuttons with LED Indicators, built-in menu system with adjusting arrows, data scrolling, data setpoint and display, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, dynamic decimal point option with read/write messages, and 20-30 VDC operating range. All the serial drivers supported.	STK	\$329 Pg 4-15
EZSeries Textpanel Manual, Programming Software, Cables and Accessories		Page 4-13
EZ-TEXT-M-E: Hardware Manual For All EZSeries Textpanels (EZ-220, EZ-420, EZ-220L, EZ-220P, EZ-220V, EZ-220V, and EZ-220PV) except EZText Setpoint Panels Note: Hardware and User Manuals Included with every EZSeries Textpanels	STK	\$25
EZ-TEXT-SP-M-E: Hardware Manual for EZSeries Textpanel Setpoint panel (EZ-SP) Only. Note: Hardware and User Manuals Included with every EZSeries Textpanels	STK	\$20
EZ-TEXTEDIT-E: Windows based Programming software for all EZSeries Textpanels. Requires Windows 95/98/NT or 2000. Manual and CD-ROM included	STK	\$28
EZTEXT-PGMCBL: Programming cable for setup and programming for all EZSeries Textpanels. 2 m (6.56ft) RS232 cable with 15-pin D-shell male connector on one end and 9-pin D-shell female connector at the other end.	STK	\$16
EZ-MULTIDROP-M: Hardware and Installation manual for EZ-Multiplexer. Included with every EZ-MULTIPLEXER purchase.	STK	\$8
EZ-TEXT-S-GSK: Replacement gasket for small EZSeries Textpanels (EZ-220, EZ-420, EZ-220V)	STK	\$8
EZ-TEXT-L-GSK: Replacement gasket for largel EZSeries Textpanels (EZ-220L, EZ-220P, EZ-SP, EZ-220PV)	STK	\$9
EZ-BRK-2: Optional DIN Rail Clips for EZSeries Textpanels, package of 4	STK	\$34



EZPLC

Part Number

	Ship	Price
EZPLC-D-96: EZPLC Snap-in I/O base with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (programming and HMI) and RS422/485 (supports ASCII In/Out), built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	3DAY	\$219 Pg 5-46
EZPLC-D-96E: EZPLC Snap-in I/O base with built-in 10 baseT Ethernet with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (Programming and HMI) and RS422/485 (supports ASCII In/Out), Built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	3DAY	\$319 Pg 5-46
DC Powered EZPLC Screw-down I/O		
EZPLCP-D-32: EZPLC Screw-down I/O base with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (programming and HMI) and RS422/485 (supports ASCII In/Out), built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for EZIO modules for a total of 32 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	STK	\$149 Pg 5-43
EZPLCPJ-D-32: EZPLC Screw-down I/O base with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, One communication port for RS232 (programming and HMI), 5 ms scan time for 1K instructions (typical), and 4 slots for EZIO modules for a total of 32 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	STK	\$89 Pg 5-43
EZPLCP-D-32E: EZPLC Screw-down I/O base with built-in 10 baseT Ethernet with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (Programming and HMI) and RS422/485 (supports ASCII In/Out), Built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for EZIO modules for a total of 32 I/O Max (based on the type of EZIO modules utilized).	3DAY	\$249 Pg 5-43
EZPLCP-D-48: EZPLC Screw-down I/O base with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (programming and HMI) and RS422/485 (supports ASCII In/Out), built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 6 slots for EZIO modules for a total of 48 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	STK	\$199 Pg 5-44
EZPLCP-D-48E: EZPLC Screw-down I/O base with built-in 10 baseT Ethernet with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (Programming and HMI) and RS422/485 (supports ASCII In/Out), Built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 6 slots for EZIO modules for a total of 48 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	3DAY	\$299 Pg 5-44
EZPLCP-D-64: EZPLC Screw-down I/O base with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (programming and HMI) and RS422/485 (supports ASCII In/Out), built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 8 slots for EZIO modules for a total of 64 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	STK	\$225 Pg 5-45
EZPLCP-D-64E: EZPLC Screw-down I/O base with built-in 10 baseT Ethernet with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (Programming and HMI) and RS422/485 (supports ASCII In/Out), Built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 8 slots for EZIO modules for a total of 64 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	3DAY	\$325 Pg 5-45
EZPLCP-D-96: EZPLC Screw-down I/O base with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (programming and HMI) and RS422/485 (supports ASCII In/Out), built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	3DAY	\$259 Pg 5-46
EZPLCP-D-96E: EZPLC Screw-down I/O base with built-in 10 baseT Ethernet with 32 Bit 40 MHz processor, 20-30 VDC power supply, 64K words total memory, two integrated communication ports for RS232 (Programming and HMI) and RS422/485 (supports ASCII In/Out), Built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used).	3DAY	\$359 Pg 5-46
Communication Interface Modules (EZPLC Only) Page 8-10, 8-37		
EZIO-LINK-CBL: Plug-in and removable terminal block cable. Sold separately. Pg 5-10	STK	\$25
EZIO-LINK-RLY: 8 of 10 Amp Relays 1 Form C Pg 5-10	STK	\$69
EZIO-LINK-EXT: 11-pin Extender Board. Pg 5-10	STK	\$29
EZPLC-DEVICENET: DeviceNet slave communication interface card for EZPLC ONLY. 5 point removable terminal block	STK	\$79
EZPLC-PROFIBUS: Profibus DP slave communication interface card for EZPLC ONLY. Standard 9-pin female D-sub connector allows baud rates up to 12MB with auto baud rate detection.	3DAY	\$129
EZPLC Manual, Programming Software, Cables, and Accessories Page 8-37		
EZPLC-M: Hardware User Manual For EZPLC - All Models. Note: EZPLCs are shipped WITHOUT User Manual. Sold separately	STK	\$30
EZPLC-CM: Hardware User Manual For DeviceNet, Profibus, and Ethernet Options	STK	\$25
EZPLC-EDIT: EZPLC Programming Software	STK	\$49
EZP-PGMCBL: Programming Cable	STK	\$20
EZPLC-BAT: Replacement Battery	STK	\$20
EZPLC-TERM5: RS422/485 5-point Terminal Block	STK	\$4

Price List

EZSeries TouchPLC

		Page 6-26
6" White on Blue Snap-in I/O		
EZP-S6W-RS-PLC: EZSeries TouchPLC Snap-in I/O with Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 cell touch screen, 256 KB of HMI RAM (non-expandable), Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	STK	\$510
EZP-S6W-RS-PLC-E: EZSeries TouchPLC Snap-in I/O with built-in Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 cell touch screen, 256 KB of HMI RAM (non-expandable), Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	3DAY	\$609
EZP-S6W-RS-PLC-D: EZSeries TouchPLC Snap-in I/O with built-in DeviceNet Slave comm interface, Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 cell touch screen, 256 KB of HMI RAM (non-expandable), Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	3DAY	\$589
EZP-S6W-RS-PLC-P: EZSeries TouchPLC Snap-in I/O with built-in Profibus DP Slave comm interface, Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 cell touch screen, 256 KB of HMI RAM (non-expandable), Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	3DAY	\$639
6" White on Blue Screw-down I/O		
EZPP-S6W-RS-PLC: EZSeries TouchPLC Screw-down I/O with Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 cell touch screen, 256 KB of HMI RAM (non-expandable), Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	STK	\$569
EZPP-S6W-RS-PLC-E: EZSeries TouchPLC Screw-down I/O with built-in Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 cell touch screen, 256 KB of HMI RAM (non-expandable), Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	3DAY	\$659
EZPP-S6W-RS-PLC-D: EZSeries TouchPLC Screw-down I/O with built-in DeviceNet Slave comm interface, Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 cell touch screen, 256 KB of HMI RAM (non-expandable), Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3ms scan time for 1K instructions (typical), 4 slots for EZIO modules for total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	3DAY	\$639
EZPP-S6W-RS-PLC-P: EZSeries TouchPLC Screw-down I/O with built-in Profibus DP Slave comm interface, Slim Bezel, 5.7" STN White on Blue display, NEMA 4,4x (indoor), 48 cell touch screen, 256 KB of HMI RAM (non-expandable), Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	3DAY	\$689
6" STN Monochrome Snap-in I/O		
EZP-S6M-FS-PLC: EZSeries TouchPLC Snap-in I/O with Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell touch screen, 512 KB of HMI RAM, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	STK	\$662
EZP-S6M-FS-PLC-E: EZSeries TouchPLC Snap-in I/O with built-in Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, Slim Bezel, 5.7" STN Monochrome display, NEMA 4,4x (indoor), 192 cell touch screen, 512 KB of HMI RAM, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), 4 slots for EZIO modules for a total of 32 I/O Max, and 20-30VDC power supply. Same Programming port for Touchpanel & PLC	3DAY	\$761



EZSeries TouchPLC

Part Number	Ship	Price
EZSeries TouchPLC Manual, Programming Software, Cables and Accessories Page 6-23		
EZP-TOUCHPLC-M: Hardware User Manual for EZSeries TouchPLCs. Note: EZP-EZSeries TouchPLC-M Hardware User Manual included with all EZSeries TouchPLCs.	STK	\$35
EZP-TOUCHPLC-EDIT: Programming Software for EZSeries TouchPLC	STK	\$99
EZP-PGMCBL: Programming Cable	STK	\$20
EZPLC, EZSeries TouchPLC, and EZSeries TextPLC Accessories Page 6-23		
EZPLC-BAT: Replacement Battery	STK	\$20
EZPLC-TERM5: RS422/485 5-point Terminal Block	STK	\$4
EZPLC-DNTERM5: DeviceNet 5-Pin Field Terminal Block for DeviceNet Interface Card - EZPLCs Only	STK	\$8

Note: For EZSeries TouchPLC and EZSeries TextPLC Mounting Hardware Accessories, refer to EZSeries Touchpanel Accessories Section on Page 2-13

EZIO

Specialty Snap-in I/O Modules	Page 7-28, 7-29, 7-30, 7-31, 7-32	
EZIO-4THIE: 4 Channel thermocouple input Snap-in I/O module with support for J, K, S, and T type thermocouples with 0.1 degree Celcius resolution. No user power required. Page 7-28	3DAY	\$149
EZIO-RTD: 4 Channel Resistance temperature detector Snap-in I/O module. No user power required. Page 7-30	3DAY	\$179
EZIO-PRGM: Program storage Snap-in module. No user power required. Page 5-16	3DAY	\$49
EZIO-PM-P: 2 Channel Pulse module "P" type or Sourcing output Snap-in I/O. No user power required. Page 7-32	3DAY	\$179
EZIO-PM-D: 2 Channel Pulse module "D" Differential Snap-in I/O. No user power required. Page 7-32	3DAY	\$179
EZIO-HSCM1: High Speed 24-Bit Counter Snap-in I/O module with support for 2 high speed quadrature encoders up to 60 KHz. 2 High speed outputs per encoder input. Page 7-29	3DAY	\$99
EZIO-HSCM2: High Speed 24-Bit Counter Snap-in I/O module with support for 1 high speed quadrature encoder up to 100 KHz. Inhibit Input, Reset Input, Pre-Set Input, and 4 High Speed Outputs. Page 7-29	3DAY	\$99
Specialty Screw-down I/O Modules	Page 7-28, 7-29, 7-30, 7-31, 7-32	
EZIOP-4THI: 4 Channel thermocouple input Screw-down I/O module with support for J, K, S, and T type thermocouples with 0.1 degree Celcius resolution. No user power required. Page 7-28	3DAY	\$149
EZIOP-RTD: 4 Channel Resistance temperature detector Snap-in I/O module. No user power required. Page 7-30	3DAY	\$179
EZIOP-PRGM: Program storage Snap-in module. No user power required. Page 5-16	3DAY	\$49
EZIOP-PM-P: 2 Channel Pulse module "P" type or Sourcing output Screw-down I/O. No user power required. Page 7-32	3DAY	\$179
EZIOP-PM-D: 2 Channel Pulse module "D" Differential Screw-down I/O. No user power required. Page 7-32	3DAY	\$179
EZIOP-HSCM1: High Speed 24-Bit Counter Screw-down I/O module with support for 2 high speed quadrature encoders up to 60 KHz. 2 High speed outputs per encoder input. Page 7-29	3DAY	\$99
EZIOP-HSCM2: High Speed 24-Bit Counter Screw-down I/O module with support for 1 high speed quadrature encoder up to 100 KHz. Inhibit Input, Reset Input, Pre-Set Input, and 4 High Speed Outputs. Page 7-29	3DAY	\$99
DC Snap-in I/O Modules	Page 7-8 to 7-14	
EZIO-8DCI: 8 point 10-28 VDC Inputs (sink/source) Snap-in I/O Page 7-8	STK	\$22
EZIO-8DCOP: 8 point 10-28 VDC (source) Outputs Snap-in I/O, 0.5 Amp per point, 1.0 Amp per module. Page 7-9	STK	\$22
EZIO-8DCON: 8 point 10-28 VDC (sink) Outputs Snap-in I/O, 0.5 Amp per point, 1.4 Amp max per module. Page 7-10	STK	\$22
EZIO-8HSDCI: 8 point High Speed 10-28 VDC Inputs (sink/source) Snap-in I/O, OFF to ON response=0.3 ms (typ). Page 7-11	STK	\$27
EZIO-4DCI4DCON: 4 point 10-28 VDC (sink/source) Inputs Snap-in I/O; 4 point 10-28 VDC (sink) outputs, 0.5 Amp per point, 1.4 Amp max for 4 outputs. Page 7-12	STK	\$22
EZIO-4DCI4DCIF: 4 point 10-28 VDC (sink/source) Inputs Snap-in I/O, OFF to ON response=3 ms (typ); 4 point High Speed 10-28 VDC (sink/source) Inputs, OFF to ON response=0.3 ms (typ); Fast input # 8 initiates fast interrupt of 20 μ s. Pg 9-13	STK	\$27
EZIO-4DCI4DCOP: 4 point 10-28 VDC (Sink/Source) Inputs Snap-in I/O; 4 point 10-28 VDC (source) outputs, 0.5 Amp per point, 1 Amp max for 4 DC Outputs. Page 7-14	STK	\$22
DC Screw-down I/O Modules	Page 7-8 to 7-14	
EZIOP-8DCI: 8 point 10-28 VDC Inputs (sink/source) Screw-down I/O Page 7-8	STK	\$29
EZIOP-8DCOP: 8 point 10-28 VDC (source) Outputs Screw-down I/O, 0.5 Amp per point, 1.0 Amp per module. Page 7-9	STK	\$29
EZIOP-8DCON: 8 point 10-28 VDC (sink) Outputs Screw-down I/O, 0.5 Amp per point, 1.4 Amp max per module. Page 7-10	STK	\$29
EZIOP-8HSDCI: 8 point High Speed 10-28 VDC Inputs (sink/source) Screw-down I/O, OFF to ON response=0.3 ms (typ). Page 7-11	STK	\$34
EZIOP-4DCI4DCON: 4 point 10-28 VDC (sink/source) Inputs Screw-down I/O; 4 point 10-28 VDC (sink) outputs, 0.5 Amp per point, 1.4 Amp max for 4 outputs. Page 7-12	STK	\$29
EZIOP-4DCI4DCIF: 4 point 10-28 VDC (sink/source) Inputs Screw-down I/O, OFF to ON response=3 ms (typ); 4 point High Speed 10-28 VDC (sink/source) Inputs, OFF to ON response=0.3ms; Fast input # 8 initiates fast interrupt of 20 μ s. Pg 9-13	STK	\$34
EZIOP-4DCI4DCOP: 4 point 10-28 VDC (Sink/Source) Inputs Screw-down I/O; 4 point 10-28 VDC (source) outputs, 0.5 Amp per point, 1 Amp max for 4 DC Outputs. Page 7-14	STK	\$29
AC Snap-in I/O Modules	Page 7-15 to 7-17	
EZIO-8ACI: 8 point 70-132 VAC Inputs Snap-in I/O. Page 7-15	STK	\$34
EZIO-8ACO: 8 point 70-132 VAC Outputs Snap-in I/O, 1.0 Amp per point. Page 7-16	STK	\$34
EZIO-4ACI4ACO: 4 point 70-132 VAC Inputs Snap-in I/O; 4 point 70-132 VAC Outputs, 1.0 Amp per point for AC Outputs. Page 7-17	STK	\$34
AC Screw-down I/O Modules	Page 7-15 to 7-17	
EZIOP-8ACI: 8 point 70-132 VAC Inputs Screw-down I/O. Page 7-15	STK	\$39
EZIOP-8ACO: 8 point 70-132 VAC Outputs Screw-down I/O, 1.0 Amp per point. Page 7-16	STK	\$39
EZIOP-4ACI4ACO: 4 point 70-132 VAC Inputs Screw-down I/O; 4 point 70-132 VAC Outputs, 1.0 Amp per point for AC Outputs. Page 7-17	STK	\$39
AC/DC Snap-in I/O Combo Modules	Page 7-18 to 7-20	
EZIO-4DCOP4ACO: 4 point 10-28VDC (source) outputs Snap-in I/O, 0.5 Amp per point, 1 Amp max for 4 DC outputs; 4 point 70-132 VAC outputs 1.0 Amp per point for AC Outputs. Page 7-18	STK	\$34
EZIO-4ACI4DCOP: 4 point 70-132 VAC Inputs Snap-in I/O; 4 point 10-28VDC (source) outputs, 0.5 Amp per point, 1 Amp max for 4 DC outputs. Page 7-19	STK	\$34
EZIO-4DCI4ACO: 4 point 10-28 VDC (sink/source) Inputs Snap-in I/O; 4 point 70-132 VAC Outputs, 1.0 Amp per point for AC Outputs. Page 7-20	STK	\$34
AC/DC Screw-down I/O Combo Modules	Page 7-18 to 7-20	
EZIOP-4DCOP4ACO: 4 point 10-28VDC (source) outputs Screw-down I/O, 0.5 Amp per point, 1 Amp max for 4 DC outputs; 4 point 70-132 VAC outputs 1.0 Amp per point for AC Outputs. Page 7-18	STK	\$44
EZIOP-4ACI4DCOP: 4 point 70-132 VAC Inputs Screw-down I/O; 4 point 10-28VDC (source) outputs, 0.5 Amp per point, 1 Amp max for 4 DC outputs. Page 7-19	STK	\$44
EZIOP-4DCI4ACO: 4 point 10-28 VDC (sink/source) Inputs Screw-down I/O; 4 point 70-132 VAC Outputs, 1.0 Amp per point for AC Outputs. Page 7-20	STK	\$44
Analog Snap-in I/O Modules	Page 7-24 to 7-27	
EZIO-8ANIV: 8 channel Analog Input module (Voltage) Snap-in I/O, 12 bit resolution; Range: 0-5VDC, 0-10VDC (switch selectable). Page 7-24	STK	\$109
EZIO-8ANIC: 8 channel Analog Input module (Current) Snap-in I/O, 12 bit resolution; Range:0-20 mA, 4-20mA (switch selectable). Page 7-25	STK	\$109
EZIO-4ANI4ANOV: 4 Channel Analog Inputs; 4 Channel Analog Outputs Snap-in I/O; 12-Bit resolution, 0-5VDC or 0-10VDC (switch selectable). Page 7-26	STK	\$109
EZIO-4ANI4ANOC: 4 Channel Analog Inputs; 4 Channel Analog Outputs Snap-in I/O; 12-Bit resolution, 0-20 mA or 4-20mA (switch selectable). Page 7-27	3DAY	\$109



EZIO

Analog Screw-down I/O Modules		Page 7-24 to 7-27
EZIO-8ANIV: 8 channel Analog Input module (Voltage) Screw-down I/O, 12 bit resolution; Range: 0-5VDC, 0-10VDC (switch selectable). Page 7-24	STK	\$119
EZIO-8ANIC: 8 channel Analog Input module (Current) Screw-down I/O, 12 bit resolution; Range: 0-20 mA, 4-20mA (switch selectable). Page 7-25	STK	\$119
EZIO-4ANI4ANOV: 4 Channel Analog Inputs; 4 Channel Analog Outputs Screw-down I/O; 12-Bit resolution, 0-5VDC or 0-10VDC (switch selectable). Page 7-26	STK	\$119
EZIO-4ANI4ANOC: 4 Channel Analog Inputs; 4 Channel Analog Outputs Screw-down I/O; 12-Bit resolution, 0-20 mA or 4-20mA (switch selectable). Page 7-27	3DAY	\$119
Relay Snap-in I/O Modules		Page 7-21 to 7-23
EZIO-4RLO: 4 point Relay Outputs Snap-in I/O, 5-180 VDC Max or 20-132 VAC; 4 Relays with Electrostatic Field Protection, Normally open (NO) contacts, 1.0 Amp Max Carry current per output.. Pg 9-21	STK	\$39
EZIO-4ACI4RLO: 4 point 70-132 VAC Inputs Snap-in I/O; 4 point Relay Outputs, 5-180 VDC Max or 20-132 VAC; 4 Relays with Electrostatic Field Protection, Normally open (NO) contacts, 1.0 Amp Max Carry current per output.. Pg 9-22	STK	\$44
EZIO-4DCIP4RLO: 4 point 10-28 VDC (sink/source) Inputs; 4 point Relay Outputs Snap-in I/O, 5-180 VDC Max or 20-132 VAC; 4 Relays with Electrostatic Field Protection, Normally open (NO) contacts, 1.0 Amp Max Carry current per output.. Pg 9-23	STK	\$44
Relay Screw-down I/O Modules		Page 7-21 to 7-23
EZIO-4RLO: 4 point Relay Outputs Screw-down I/O, 5-180 VDC Max or 20-132 VAC; 4 Relays with Electrostatic Field Protection, Normally open (NO) contacts, 1.0 Amp Max Carry current per output.. Pg 9-21	STK	\$49
EZIO-4ACI4RLO: 4 point 70-132 VAC Inputs; 4 point Relay Outputs Screw-down I/O, 5-180 VDC Max or 20-132 VAC; 4 Relays with Electrostatic Field Protection, Normally open (NO) contacts, 1.0 Amp Max Carry current per output.. Pg 9-22	STK	\$54
EZIO-4DCIP4RLO: 4 point 10-28 VDC (sink/source) Inputs; 4 point Relay Outputs Screw-down I/O, 5-180 VDC Max or 20-132 VAC; 4 Relays with Electrostatic Field Protection, Normally open (NO) contacts, 1.0 Amp Max Carry current per output.. Pg 9-23	STK	\$54
EZIO Manual and Accessories		Page 7- 4
EZIO-LINK-CBL: Plug-in and removable terminal block cable. Sold separately. Pg 5-10	STK	\$25
EZIO-LINK-RLY: 8 of 10 Amp Relays 1 Form C Pg 5-10	STK	\$69
EZIO-LINK-EXT: 11-pin Extender Board. Pg 5-10	STK	\$29
EZIO-M: Hardware Manual for EZIO Modules. Note: EZIO Modules are shipped without User Manual. Sold separately	STK	\$25
EZIO-DUMMY: Dummy Module for EZPLC, EZSeries TouchPLC, and EZSeries TextPLC Open Slots	STK	\$5
EZIO-TERM11: 11 Pin Removable 3.5mm Phoenix Terminal Block for EZIO Modules	STK	\$5
EZIO-TERM11CJC: 11 Pin Removable 3.5mm Phoenix Terminal Block for Thermocouple Module with Built-in Cold Junction Compensator	STK	\$15
EZIO-SCDRV: Pack of two 2.5mm blade screwdrivers for EZIO's Phoenix Terminal Blocks	STK	\$5

Price List

EZRIO

AC Powered EZRIO Snap-in I/O		
EZRIO-A-32: EZRIO Snap-in I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 4 slots for EZIO modules for a total of 32 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$129 Pg 8-11
EZRIO-A-32E: EZRIO Snap-in I/O Enhanced base with built-in 10 baseT Ethernet, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 4 slots for EZIO modules for a total of 32 I/O Max (based on the type of EZIO modules utilized). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$228 Pg 8-11
EZRIO-A-48: EZRIO Snap-in I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 6 slots for EZIO modules for a total of 48 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$168 Pg 8-12
EZRIO-A-48E: EZRIO Snap-in I/O Enhanced base with built-in 10 baseT Ethernet, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 6 slots for EZIO modules for a total of 48 I/O Max (based on the type of EZIO modules utilized). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$267 Pg 8-12
EZRIO-A-64: EZRIO Snap-in I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 8 slots for EZIO modules for a total of 64 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$188 Pg 8-13
EZRIO-A-64E: EZRIO Snap-in I/O Enhanced base with built-in 10 baseT Ethernet, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 8 slots for EZIO modules for a total of 64 I/O Max (based on the type of EZIO modules utilized). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$287 Pg 8-13
EZRIO-A-96: EZRIO Snap-in I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	3DAY	\$219 Pg 8-14
EZRIO-A-96E: EZRIO Snap-in I/O Enhanced base with built-in 10 baseT Ethernet, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 12 slots for EZIO modules for a total of 96 I/O Max (based on the type of EZIO modules utilized). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$318 Pg 8-14
AC Powered EZRIO Screw-down I/O		
EZRIO-A-32: EZRIO Screw-down I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 4 slots for EZIO modules for a total of 32 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$159 Pg 8-11
EZRIO-A-32E: EZRIO Screw-down I/O Enhanced base with built-in 10 baseT Ethernet, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 4 slots for EZIO modules for a total of 32 I/O Max (based on the type of EZIO modules utilized). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$259 Pg 8-11
EZRIO-A-48: EZRIO Screw-down I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 6 slots for EZIO modules for a total of 48 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$225 Pg 8-12
EZRIO-A-48E: EZRIO Screw-down I/O Enhanced base with built-in 10 baseT Ethernet, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 6 slots for EZIO modules for a total of 48 I/O Max (based on the type of EZIO modules utilized). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$325 Pg 8-12
EZRIO-A-64: EZRIO Screw-down I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 8 slots for EZIO modules for a total of 64 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$249 Pg 10-13
EZRIO-A-64E: EZRIO Screw-down I/O Enhanced base with built-in 10 baseT Ethernet, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 8 slots for EZIO modules for a total of 64 I/O Max (based on the type of EZIO modules utilized). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$349 Pg 8-13
EZRIO-A-96: EZRIO Screw-down I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	3DAY	\$289 Pg 8-14
EZRIO-A-96E: EZRIO Screw-down I/O, 96-120 VAC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	3DAY	\$389 Pg 8-14
DC Powered EZRIO Snap-in I/O		
EZRIO-D-32: EZRIO Snap-in I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 4 slots for EZIO modules for a total of 32 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$111 Pg 8-11
EZRIO-D-32E: EZRIO Snap-in I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 4 slots for EZIO modules for a total of 32 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$210 Pg 8-11
EZRIO-D-48: EZRIO Snap-in I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 6 slots for EZIO modules for a total of 48 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$150 Pg 8-12
EZRIO-D-48E: EZRIO Snap-in I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 6 slots for EZIO modules for a total of 48 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$249 Pg 8-12
EZRIO-D-64: EZRIO Snap-in I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 8 slots for EZIO modules for a total of 64 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$170 Pg 8-13
EZRIO-D-64E: EZRIO Snap-in I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 8 slots for EZIO modules for a total of 64 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$269 Pg 8-13



EZRIO

Part Number	Ship	Price
EZRIO-D-96: EZRIO Snap-in I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	3DAY	\$190 Pg 8-14
EZRIO-D-96E: EZRIO Snap-in I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$289 Pg 8-14
DC Powered EZRIO Screw-down I/O		
EZRIO-D-32: EZRIO Screw-down I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 4 slots for EZIO modules for a total of 32 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$149 Pg 8-11
EZRIO-D-32E: EZRIO Screw-down I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 4 slots for EZIO modules for a total of 32 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$249 Pg 8-11
EZRIO-D-48: EZRIO Screw-down I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 6 slots for EZIO modules for a total of 48 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$199 Pg 8-12
EZRIO-D-48E: EZRIO Screw-down I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 6 slots for EZIO modules for a total of 48 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$299 Pg 8-12
EZRIO-D-64: EZRIO Screw-down I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 8 slots for EZIO modules for a total of 64 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	STK	\$225 Pg 8-13
EZRIO-D-64E: EZRIO Screw-down I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 8 slots for EZIO modules for a total of 64 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$325 Pg 8-13
EZRIO-D-96: EZRIO Screw-down I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus RTU and EZ Protocols	3DAY	\$259 Pg 8-14
EZRIO-D-96E: EZRIO Screw-down I/O, 20-30 VDC power supply, 64K words total memory, two communication ports for RS232 and RS422/485, 12 slots for EZIO modules for a total of 96 I/O Max (maximum number of I/O points vary based on the type of EZIO modules used). Modbus TCP/IP, Ethernet IP and EZ IP Protocols	3DAY	\$359 Pg 8-14
EZRIO Manual, Communication Modules and Accessories		
Page 8-37		
EZRIO-M: Hardware User Manual For EZRIO - All Models. Note: EZRIOs are shipped WITHOUT User Manual. Sold separately	STK	\$30
EZRIO-CM: Hardware User Manual For DeviceNet, Profibus, and Ethernet Options	STK	\$25
EZRIO-TERM5: RS422/485 5-point Terminal Block	STK	\$4
EZPLC-DEVICENET: DeviceNet slave communication interface card for EZRIO ONLY. 5 point removable terminal block	STK	\$79
EZPLC-PROFIBUS: Profibus DP slave communication interface card for EZRIO ONLY. Standard 9-pin female D-sub connector allows baud rates up to 12MB with auto baud rate detection.	3DAY	\$129

EZSeries TextPLC

220 EZSeries TextPLC Snap-in I/O	Page 9-21	
EZ-220-PLC: EZSeries TextPLC with 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Snap-in EZIO modules for a total of 32 I/O Max.	STK	\$272
EZ-220-PLC-E: EZSeries TextPLC with built-in Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Snap-in EZIO modules for a total of 32 I/O Max.	3DAY	\$371
EZ-220-PLC-D: EZSeries TextPLC with built-in DeviceNet Slave comm interface, 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Snap-in EZIO modules for a total of 32 I/O Max.	3DAY	\$351
EZ-220-PLC-P: EZSeries TextPLC with built-in Profibus DP Slave comm interface, 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Snap-in EZIO modules for a total of 32 I/O Max.	3DAY	\$401
220 EZSeries TextPLC Screw-down I/O		
Page 9-21		
EZP-220-PLC: EZSeries TextPLC with 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Screw-down EZIO modules for a total of 32 I/O Max.	STK	\$302
EZP-220-PLC-E: EZSeries TextPLC with built-in Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Screw-down EZIO modules for a total of 32 I/O Max.	3DAY	\$401
EZP-220-PLC-D: EZSeries TextPLC with built-in DeviceNet Slave comm interface, 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Screw-down EZIO modules for a total of 32 I/O Max.	3DAY	\$381
EZP-220-PLC-P: EZSeries TextPLC with built-in Profibus DP Slave comm interface, 2 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Screw-down EZIO modules for a total of 32 I/O Max.	3DAY	\$431
420 EZSeries TextPLC Snap-in I/O		
Page 9-21		
EZ-420-PLC: EZSeries TextPLC with 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Snap-in EZIO modules for a total of 32 I/O Max.	STK	\$292
EZ-420-PLC-E: EZSeries TextPLC with built-in Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Snap-in EZIO modules for a total of 32 I/O Max.	3DAY	\$391
EZ-420-PLC-D: EZSeries TextPLC with built-in DeviceNet Slave comm interface, 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Snap-in EZIO modules for a total of 32 I/O Max.	3DAY	\$371
EZ-420-PLC-P: EZSeries TextPLC with built-in Profibus DP Slave comm interface, 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Snap-in EZIO modules for a total of 32 I/O Max.	3DAY	\$421
420 EZSeries TextPLC Screw-down I/O		
Page 9-21		
EZP-420-PLC: EZSeries TextPLC with 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, built-in real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Screw-down EZIO modules for a total of 32 I/O Max.	STK	\$322
EZP-420-PLC-E: EZSeries TextPLC with built-in Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Screw-down EZIO modules for a total of 32 I/O Max.	3DAY	\$421
EZP-420-PLC-D: EZSeries TextPLC with built-in DeviceNet Slave comm interface, 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Screw-down EZIO modules for a total of 32 I/O Max.	3DAY	\$401
EZP-420-PLC-P: EZSeries TextPLC with built-in Profibus DP Slave comm interface, 4 Line x 20 character LCD Display, Nema 4,4x (indoor) front, five user defined pushbuttons with LED Indicators, arrow adjust, 256 programmable messages with up to 2 embedded read only data points and 1 read/write data point per message, Built-in high performance PLC with RS422/ASCII port, real time clock/Calendar, 3 ms scan time for 1K instructions (typical), and 4 slots for Screw-down EZIO modules for a total of 32 I/O Max.	3DAY	\$451



EZMarquee

Part Number	Ship	Price
EZMT-4L20C-P-OUT: 4 Lines of 2" charac, 20 charc per line, TRI-COLOR LED Outdoor, Profibus DP Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$4059
4 Line 40 Char Page 10-50 Page 10-51		
EZMR-4L40C: 4 Lines of 2" charac, 40 charc per line, RED LED, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$2399
EZMR-4L40C-E: 4 Lines of 2" charac, 40 charc per line, RED LED, Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$2498
EZMR-4L40C-D: 4 Lines of 2" charac, 40 charc per line, RED LED, DeviceNet Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$2498
EZMR-4L40C-P: 4 Lines of 2" charac, 40 charc per line, RED LED, Profibus DP Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$2548
EZMRH-4L40C: 4 Lines of 2" charac, 40 charc per line, RED LED High-bright, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$4799
EZMRH-4L40C-E: 4 Lines of 2" charac, 40 charc per line, RED LED High-bright, Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$4999
EZMRH-4L40C-D: 4 Lines of 2" charac, 40 charc per line, RED LED High-bright, DeviceNet Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$4999
EZMRH-4L40C-P: 4 Lines of 2" charac, 40 charc per line, RED LED High-bright, Profibus DP Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$5099
EZMR-4L40C-OUT: 4 Lines of 2" charac, 40 charc per line, RED LED Outdoor, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$4799
EZMR-4L40C-E-OUT: 4 Lines of 2" charac, 40 charc per line, RED LED Outdoor, Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$4999
EZMR-4L40C-D-OUT: 4 Lines of 2" charac, 40 charc per line, RED LED Outdoor, DeviceNet Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$4999
EZMR-4L40C-P-OUT: 4 Lines of 2" charac, 40 charc per line, RED LED Outdoor, Profibus DP Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$5099
EZMRH-4L40C-OUT: 4 Lines of 2" charac, 40 charc per line, RED LED High-bright, Outdoor, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$7199
EZMRH-4L40C-E-OUT: 4 Lines of 2" charac, 40 charc per line, RED LED High-bright, Outdoor, Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$7499
EZMRH-4L40C-D-OUT: 4 Lines of 2" charac, 40 charc per line, RED LED High-bright, Outdoor, DeviceNet Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$7499
EZMRH-4L40C-P-OUT: 4 Lines of 2" charac, 40 charc per line, RED LED High-bright, Outdoor, Profibus DP Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$7659
EZMT-4L40C: 4 Lines of 2" charac, 40 charc per line, TRI-COLOR LED, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$3299
EZMT-4L40C-E: 4 Lines of 2" charac, 40 charc per line, TRI-COLOR LED, Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$3398
EZMT-4L40C-D: 4 Lines of 2" charac, 40 charc per line, TRI-COLOR LED, DeviceNet Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$3398
EZMT-4L40C-P: 4 Lines of 2" charac, 40 charc per line, TRI-COLOR LED, Profibus DP Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 12 housing.	7DAY	\$3448
EZMT-4L40C-OUT: 4 Lines of 2" charac, 40 charc per line, TRI-COLOR LED Outdoor, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$6598
EZMT-4L40C-E-OUT: 4 Lines of 2" charac, 40 charc per line, TRI-COLOR LED Outdoor, Ethernet with Ethernet IP, Modbus TCP/IP, EZIP & TCP/IP protocols, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$6799
EZMT-4L40C-D-OUT: 4 Lines of 2" charac, 40 charc per line, TRI-COLOR LED Outdoor, DeviceNet Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$6799
EZMT-4L40C-P-OUT: 4 Lines of 2" charac, 40 charc per line, TRI-COLOR LED Outdoor, Profibus DP Slave comm interface, two built-in comm ports RS232 and RS422/485, Nema 4 housing.	14DAY	\$6899
EZMarquee Manual, Programming Software, Cables and Accessories Page 10-23		
EZM-MARQUEE-M: Hardware User Manual for EZMarquees. Note: EZM-EZMarquee-M Hardware User Manual is not included with EZMarquees.	STK	\$30
EZM-GRMT: Grommets for EZMarquee Back Plate - All Models (package of 2)	STK	\$8
EZM-BKPLT: Back Plate with Gasket for EZMarquees - All Models. Does not include grommets	STK	\$10
EZM-TERM5: RS422/485 Terminal Block for EZMarquee - All Models	STK	\$4
EZM-MNTBRK1: Mounting Brakets for EZMarquees - 1L10C and 1L20C Models Only (package of 2)	STK	\$16
EZM-MNTBRK2: Mounting Brakets for EZMarquees - 2L10C and 2L20C Models Only (package of 2)	STK	\$20

Price List

EZSeries CE Touch Computer

6" White On Blue Page 11-13	
EZTCC-S6W-S: EZTouchscreen CE Computer with Slim Bezel, 5.7" STN White on Blue display, pre-loaded with Win CE.net 4.2 core, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$599
EZTCC-S6W-E: EZTouchscreen CE Computer Enhanced with Slim Bezel, 5.7" STN White on Blue display, pre-loaded with Win CE.net Professional Plus, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$699
6" Monochrome Page 11-14	
EZTCC-S6M-S: EZTouchscreen CE Computer with Slim Bezel, 5.7" STN Monochrome display, pre-loaded with Win CE.net 4.2 core, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$749
EZTCC-S6M-E: EZTouchscreen CE Computer Enhanced with Slim Bezel, 5.7" STN Monochrome display, pre-loaded with Win CE.net Professional Plus, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$849
6" STN Color Page 11-15	
EZTCC-S6C-S: EZTouchscreen CE Computer with Slim Bezel, 5.7" STN Color display, pre-loaded with Win CE.net 4.2 core, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$899
EZTCC-S6C-E: EZTouchscreen CE Computer Enhanced with Slim Bezel, 5.7" STN Color display, pre-loaded with Win CE.net Professional Plus, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$999
6" TFT Color Page 11-16	
EZTCC-T6C-S: EZTouchscreen CE Computer with Slim Bezel, 5.7" TFT Color display, pre-loaded with Win CE.net 4.2 core, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$1,199
EZTCC-T6C-E: EZTouchscreen CE Computer Enhanced with Slim Bezel, 5.7" TFT Color display, pre-loaded with Win CE.net Professional Plus, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$1,299
8" STN Color Page 11-17	
EZTCC-S8C-S: EZTouchscreen CE Computer with Slim Bezel, 8.2" STN Color display, pre-loaded with Win CE.net 4.2 core, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY \$1,299



EZSeries CE Touch Computer

Part Number	Ship	Price
EZTCC-S8C-E: EZTouchscreen CE Computer Enhanced with Slim Bezel, 8.2" STN Color display, pre-loaded with Win CE.net Professional Plus, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY	\$1,399
8" TFT Color Page 11-18		
EZTCC-T8C-S: EZTouchscreen CE Computer with Slim Bezel, 8.2" TFT Color display, pre-loaded with Win CE.net 4.2 core, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY	\$1,499
EZTCC-T8C-E: EZTouchscreen CE Computer Enhanced with Slim Bezel, 8.2" TFT Color display, pre-loaded with Win CE.net Professional Plus, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY	\$1,599
10" TFT Color Page 11-19		
EZTCC-T10C-S: EZTouchscreen CE Computer with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net 4.2 core, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY	\$1,799
EZTCC-T10C-E: EZTouchscreen CE Computer Enhanced with Slim Bezel, 10.4" TFT Color display, pre-loaded with Win CE.net Professional Plus, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY	\$1,899
15" TFT Color Page 11-20		
EZTCC-T15C-S: EZTouchscreen CE Computer with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net 4.2 core, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY	\$1,999
EZTCC-T15C-E: EZTouchscreen CE Computer Enhanced with Slim Bezel, 15" TFT Color display, pre-loaded with Win CE.net Professional Plus, Nema 4,4x (indoor), Analog Resistive touch screen, AMD 333 MHz 32 bit processor, 64MB RAM, 32MB built-in FLASH, Compact FLASH Slot, Ethernet port, 1 USB Host port, 1 RS232 port, 1 RS232/422/485 port, and 20-30VDC operating range. EZTCC-Computer-M manual included with the computer.	3DAY	\$2,099
EZTouchscreen CE Computer Accessories Page 11-10		
EZTCC-COMPUTER-M: Hardware and Installation manual for EZTouchscreen CE Computer. This manual is included with every CE Computer. Note: Hardware and Installation included with every CE Computer.	3DAY	\$15
EZP-BAT: Replacement 1/2 AA, 3.6 volt lithium battery for EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$20
EZP-BRK-1: Optional DIN rail clips. Only for 6" models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer (package of 2).	STK	\$15
EZP-COMCON3: 15-pin male D-sub connectors with terminal blocks, for connecting RS422 network cable to EZ Products	STK	\$19
EZP-PANEL6-GSK: Replacement gasket for 6-inch EZPanel Enhanced operator interface (standard, NON-SLIM) bezels only.	STK	\$8
EZP-PANEL8-GSK: Replacement gasket for 8-inch EZPanel Enhanced operator interface (standard, NON-SLIM) bezels only.	STK	\$8
EZP-PANEL10-GSK: Replacement gasket for 10-inch EZPanel Enhanced operator interface (standard, NON-SLIM) bezels only.	STK	\$8
EZP-PANEL-STUDS: Spare mounting studs for for EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer panels. Comes in package of 8 with nuts.	STK	\$8
EZP-6SLIMF-GSK: Replacement gasket for Slim Bezel 6 inch models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer.	STK	\$8
EZP-8SLIMF-GSK: Replacement gasket for Slim Bezel 8 inch models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer.	STK	\$25
EZP-10SLIMF-GSK: Replacement gasket for Slim Bezel 10 inch models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer.	STK	\$30
EZP-15SLIMF-GSK: Replacement gasket for Slim Bezel 15 inch models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer.	STK	\$34
EZP-COV6: Pack of 3 protective shields for 6 inch models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$20
EZP-COV8: Pack of 3 protective shields for 8 inch models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$34
EZP-COV10: Pack of 3 protective shields for 10 inch models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$38
EZP-COV15: Pack of 3 protective shields for 15 inch models of EZPanel Enhanced, EZCE Touchpanel, and EZTouchscreen CE Computer	STK	\$56

EZMonitor

EZMonitor		
EZ-10M: 10.4" SVGA TFT Color Display (600 vertical by 800 horizontal pixel array), 262,144 colors, 220cd/m2 (Typ.), Contrast Ratio of 400:1, Industrial housing with Nema 4/4x front. Page 12-6	STK	\$999
EZ-12M: 12.1" SVGA TFT Color Display (600 vertical by 800 horizontal pixel array), 262,144 colors, 300cd/m2 (Typ.), Contrast Ratio of 200:1, Industrial housing with Nema 4/4x front. Page 12-7	STK	\$999
EZ-15M: 15" VGA TFT Color Display (768 vertical by 1024 horizontal pixel array), 16M colors, 250cd/m2 (Typ.), Contrast Ratio of 350:1, Industrial housing with Nema 4/4x front. Page 12-8	STK	\$1,099
EZ-17M: 17" SVGA TFT Color Display (1024 vertical by 1280 horizontal pixel array), 16.2M colors, 250cd/m2 (Typ.), Contrast Ratio of 400:1, Industrial housing with Nema 4/4x front. Page 12-9	STK	\$1,199
EZ-10MT: 10.4" SVGA TFT Color Display (600 vertical by 800 horizontal pixel array) with Analog Resistive Touch Screen, 262,144 colors, 220cd/m2 (Typ.) USB setup, Contrast Ratio of 400:1, Industrial housing with Nema 4/4x front. Page 12-6	STK	\$1,099
EZ-12MT: 12.1" SVGA TFT Color Display (600 vertical by 800 horizontal pixel array) with Analog Resistive Touch Screen, 262,144 colors, 300cd/m2 (Typ.) USB setup, Contrast Ratio of 200:1, Industrial housing with Nema 4/4x front. Page 12-7	STK	\$1,199
EZ-15MT: 15" VGA TFT Color Display (768 vertical by 1024 horizontal pixel array) with Analog Resistive Touch Screen, 16M colors, 250cd/m2 (Typ.) USB setup, Contrast Ratio of 350:1, Industrial housing with Nema 4/4x front. Page 12-8	STK	\$1,299
EZ-17MT: 17" SVGA TFT Color Display (1024 vertical by 1280 horizontal pixel array) with Analog Resistive Touch Screen, 16.2M colors, 250cd/m2 (Typ.) USB setup, Contrast Ratio of 400:1, Industrial housing with Nema 4/4x front. Page 12-9	STK	\$1,499
EZ-10MT-S: 10.4" SVGA TFT Color Display (600 vertical by 800 horizontal pixel array) with Analog Resistive Touch Screen, 262,144 colors, 220cd/m2 (Typ.) Serial setup, Contrast Ratio of 400:1, Industrial housing with Nema 4/4x front. Page 12-6	STK	\$1,099
EZ-12MT-S: 12.1" SVGA TFT Color Display (600 vertical by 800 horizontal pixel array) with Analog Resistive Touch Screen, 262,144 colors, 300cd/m2 (Typ.) Serial setup, Contrast Ratio of 200:1, Industrial housing with Nema 4/4x front. Page 12-7	STK	\$1,199
EZ-15MT-S: 15" VGA TFT Color Display (768 vertical by 1024 horizontal pixel array) with Analog Resistive Touch Screen, 16M colors, 250cd/m2 (Typ.) Serial setup, Contrast Ratio of 350:1, Industrial housing with Nema 4/4x front. Page 12-8	STK	\$1,299
EZ-17MT-S: 17" SVGA TFT Color Display (1024 vertical by 1280 horizontal pixel array) with Analog Resistive Touch Screen, 16.2M colors, 250cd/m2 (Typ.) Serial setup, Contrast Ratio of 400:1, Industrial housing with Nema 4/4x front. Page 12-9	STK	\$1,499
EZMonitor Accessories Page 12-5		
EZ-MPS-A: Molded design power supply: Input: 110V-240VDC at 50-60Hz, Output: 12VDC, 3.3A	STK	\$39
EZ-MPS-B: Molded design power supply: Input: 110V-240VDC at 50-60Hz, Output: 12VDC, 5A	STK	\$49
EZ-MVCBL-10: 10' shielded video cable	STK	\$29
EZ-MVCBL-25: 25' shielded video cable	STK	\$49
EZ-MVCBL-50: 50' shielded video cable	STK	\$75
EZ-TERM3: 3 Point Terminal Block Adapter for Power Input	STK	\$29