




# EZPLCX-X-32 Specifications

## EZPLC 32 I/O features:

- Highest Processing power per cubic inch.
- Incredibly condensed, 31 different combo plug-in I/O modules.
- Easiest Drag-n-Drop programming software for \$69
- Free Flow Logic cuts down number of rungs by at least 50%
- Communications galore, DeviceNet, Profibus, all Industrial Ethernet protocols. (DH+/RIO coming soon)
- Advanced functionalities, Math, High Speed counters.
- 32 bit Floating point Math and Logic
- 8 Auto tuned PID loops & unique PID monitor
- Highest processing speed, 40 $\mu$ s response to Interrupt
- RS422/485 Modbus Master Port
- Advanced instructions: Data convert, move block, bit move, strings and subroutines
- Modular Expandable to 2048 I/O
- Flash Memory Module to upload program without laptop, software or cable
- Status LED for each I/O in every model and Plug-in Terminal Blocks.



## MODULES NOT INCLUDED WITH BASE

| Model Number                              | Interface  | Price          | Del. |
|---|--|----------------|------|
| <b>EZPLCP-A-32</b><br><b>EZPLCPJ-A-32</b> | <b>AC Model – 32 I/O Base</b> comes with RS232 port 1 and RS422/485 port 2, and a Male connector for plugging in DeviceNet or Profibus option cards. Screw-down I/O. EZPLCPJ Junior models have only 1 RS232 port            | \$239<br>\$109 | STK  |
| <b>EZPLCP-A-32E</b>                       | <b>AC Model – 32 I/O Enhanced Ethernet Base</b> comes with RS232 port 1, RS422/485 port 2, Ethernet port 3 and a Male connector for plugging in DeviceNet or Profibus option cards. Screw-down I/O.                          | \$279          | 3DAY |
| <b>EZPLCP-D-32</b><br><b>EZPLCPJ-D-32</b> | <b>DC Power – 32 I/O Base</b> comes with RS232 port 1 and RS422/485 port 2, and a Male connector for plugging in DeviceNet or Profibus option cards. Screw-down I/O. EZPLCJ and EZPLCPJ Junior models have only 1 RS232 port | \$229<br>\$99  | STK  |
| <b>EZPLCP-D-32E</b>                       | <b>DC Power – 32 I/O Enhanced Ethernet Base</b> comes with RS232 port 1, RS422/485 port 2, Ethernet port 3 and a Male connector for plugging in DeviceNet or Profibus option cards. Screw-down I/O.                          | \$279          | 3DAY |

**NOTE: EZPLC Jr. has only RS232 port and no other connector**

**No limitation on I/O module location except:**

**Bottom left module cannot be AC output module \* Does not apply to EZPLC Jr.**

