

# EZPLC Micro<sup>®</sup> EZPLC Micro Specifications

## EZPLC Micro features:

- 24 DC In, 8 DC Out, 8 of 10 Amp 1 Form C Relay Outputs, 12-bit 4 Analog In & 4 Analog Out, High Speed Counter Input and RS 485 expansion port makes EZPLC Micro a "Bench Mark" for all mid-size PLCs against which all others are measured.
- Relay contacts with built-in snubbers that increase the electrical life of contacts by a factor of 10 to over 1 million
- Easiest Drag-n-Drop programming software
- Free Flow Logic cuts down number of rungs by at least 50%
- Advanced functionalities, Math, High Speed counters.
- 32 bit Floating point Math & Logic
- 8 Auto tuned PID loops and unique PID monitor
- Drum Sequencer, and send to marquee instruction
- Advanced instructions: Data convert, move block, bit move, strings and subroutines
- Password protection for OEM/SI investment
- Status LED for each I/O in every model and Plug-in Terminal Blocks.



Model Number	Interface	Price	Del.
<b>EZPLCM-D-24-8-8R</b>	EZPLC Micro, DC Powered, 24 DC Inputs, 8 DC Outputs, 8 Relay outputs	\$249	STK
<b>EZPLCM-D-F24-8-8R</b>	EZ PLC Micro, DC powered, 24 DC Inputs (2 Inputs configurable to accept 20 KHz high speed signals), 8 DC outputs, 8 Relay outputs	\$269	STK
<b>EZPLCM-D-F24-8-8R-485</b>	EZ PLC Micro, DC powered, 24 DC Inputs (2 Inputs configurable to accept 20 KHz high speed signals), 8 DC outputs, 8 Relay outputs, RS485 connector	\$299	STK
<b>EZPLCM-D-24-8-8R-4AI4AOV</b>	EZPLC Micro, DC Powered, 24 DC Inputs, 8 DC Outputs, 8 Relay outputs, 4 Analog Inputs, 4 Analog outputs (Voltage)	\$399	STK
<b>EZPLCM-D-F24-8-8R-4AI4AOV</b>	EZ PLC Micro, DC Powered, 24 DC Inputs (2 Inputs configurable to accept 20 KHz high speed signals), 8 DC outputs, 8 Relay outputs, 4 Analog Inputs, 4 Analog Outputs (Voltage)	\$399	STK
<b>EZPLCM-D-F24-8-8R-4AI4AOV-485</b>	EZ PLC Micro, DC Powered, 24 DC Inputs (2 Inputs configurable to accept 20 KHz high speed signals), 8 DC outputs, 8 Relay outputs, 4 Analog Inputs, 4 Analog Outputs (Voltage), RS485 Connector	\$399	STK
<b>EZPLCM-D-24-8-8R-2AI2AOC</b>	EZPLC Micro, DC Powered, 24 DC Inputs, 8 DC Outputs, 8 Relay outputs, 2 Analog Inputs, 2 Analog outputs (Current)	\$399	STK
<b>EZPLCM-D-F24-8-8R-2AI2AOC</b>	EZPLC Micro, DC Powered, 24 DC Inputs (2 Inputs configurable to accept 20 KHz high speed signals), 8 DC Outputs, 8 Relay outputs, 2 Analog Inputs, 2 Analog outputs (Current)	\$409	STK
<b>EZPLCM-D-F24-8-8R-2AI2AOC-485</b>	EZPLC Micro, DC Powered, 24 DC Inputs (2 Inputs configurable to accept 20 KHz high speed signals), 8 DC Outputs, 8 Relay outputs, 2 Analog Inputs, 2 Analog outputs (Current), RS485 Connector	\$409	STK

